

PRODUCT SPEC SHEET

Carpet

The Collage Collection

Collage is a 1/12th gauge Modular Carpet Tile in 4 colours that features a random rectangular design. This product co-ordinates with Linear Art. It is made of 100% Bleach Resistant Olefin with a superior stain resistance that has a fusion bonded virgin PVC backing that is reinforced with a fibreglass layer for dimensional stability. This carpet tile is solution dyed (colour fast) with a zipper free superior tuft bound and offers a lifetime warranty for delamination, dimensional stability, wear and backing.

PRODUCT INFORMATION:

Tile/Roll Size (Length x Width)	Fiber	Pattern Repeat	Carpet Type	Dye Method	Gauge	Backing	Stitches Per Inch	Pile Height	Approx. Face Weight	Recycled Content	Installation Method
19.7" x 19.7"	100% Bleach Resistant Olefin	N/A	Multi-level loop carpet tile	Solution dyed	1/10	Fusion bonded virgin PVC backing	43	2.8/5 (+0.5) mm	22 oz	N/A	Monolithic, Quarter turn, Ashlar, Brick

WARRANTY:

Wear	Delamination	Backing	Dim. Stability
Lifetime	Lifetime	Lifetime	Lifetime

PACKAGING:

Tiles/ Carton	Coverage/ Carton	Carton Dimensions (Length x Width x Height)	Carton/Roll Weight
20	53.82 sft	20" x 20" x 5.3"	25(+1) kgs

PALLET:

Cartons/ Pallet	Coverage/ Pallet
60	1506.96 sft

PERFORMANCE SPECIFICATIONS:

Reference	Result
Flammability Rating	E648-06
Smoke/Density	ASTM E 662-06
Colourfastness	AATCC TEST METHOD 165
Static rating	AATCC 134-1996
Primary Backing	Non-woven
Secondary Backing	PVC with fiber glass
Soil Resistance	N/A

SUSTAINABILITY CERTIFICATIONS: (Greenguard, Greenguard Gold, LEED, PEFC, CARB2, Floorscore, Recycled Content, Lacey & FSC)

Performance	Certifications/Credits	Minimum Requirements	Performance vs. Requirements
Sustainability	Green guard		
Air Quality	CRI		

For more information: richmondcarpet.ca

Numerical flammability ratings along may not define product performance under actual conditions. These ratings are provided only for use in the selection of products to meet specified limits.