



Oak Transparent Espresso

Product details / Technical properties

Article number	10155081 (GG4VZ3FE)	Bevel	beveled 2V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	1	Fire protection classification	Dfl-s1
Grading	Espresso	Surface structure	Brushed	Content of formaldehyde	E1
Product type	3-Layer	m² per carton	2,76	PCP content	NPD
Format	Castle plank	Boards per carton	6	Brinell Value (N/mm²)	38
Dimensions	9/16 x 8-1/4 x 86-5/8 inch	Weight per carton (kg)	21,6	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	138	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	50	Thermal conductivity (W/(m*K))	0,129
Connection	T/G	Weight per pallet (kg)	1080	Thermal resistance (m²*K)/W	0,109
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 91
Remarks	Wood is a product of nature – each tree has its own structure and individual colour combination. An image of a sample will therefore not be able to give you a complete picture of the finished floor. Please also note that the colour of the wood is exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.	FSC claim	Controlled source	Antislip performance (DIN)	83
Appearance	Golden	Performance classification	Class 1	Nobb number	
Colour	Transparent	Density	>= 500kg/m ³	EAN Code	7035580221777



Generated 06.04.2025



www.blauer-engel.de/uz176

boen.com

