

Pike's Peak



Plank 14 Colors

Tile 4 Colors










■ Product Configuration



Features

ECO- & HUMAN-FRIENDLY

- FloorScore® and DIBt certified for low VOCs
- Phthalate-Free (DEHP·DBP·BBP·DIDP·DINP·DNOP) & Heavy Metal-Free (Cd·Pb·Hg·Cr6+)
- Made from 100% virgin vinyl

EXCELLENCE IN DESIGN

- High-resolution imaging and patterns for realistic wood visuals
- Tiles mirror natural stone patterns

DURABILITY

- PUR double coating improves resistance to scratches
- 10 Years Heavy Commercial/25 Years Residential Warranty

EXCELLENT RESISTANCE TO WATER

• No swelling, no distortion

All specifications are subject to change without notice.

Application images are CGI renderings that are shown for illustration purpose only.

Printed representation of colors may vary from actual product. Please view the

Specifications

COLLECTION NAME	Pike's Peak
TOTAL # SKUs (Colors)	18 (Plank 14, Tile 4)

PRODUCT SPECIFICATIONS/CONTENT/CERTIFICATIONS	DETAILS		ADDITIONAL INFORMATION
Thickness	2.5 mm (0.098")		
Wear Layer	20 mil (0.5 mm)		
Glass Fiber	No		
Finishing/Coating	Enhanced UV Urethane Coating		
Nominal Dimensions (inches)	Plank (7" x 48"), Tile (12" x 2	24")	
Actual Dimensions (mm)	Plank (180 mm x 1,200 mm), Tile (300 mm x 600 mm)		
Micro-Beveled	No		
Class/ASTM F1700	Class III Printed Film Vinyl Tile - Type B (embossed)		
Backing Class	Commercial Grade 5 - 12 Heavy Commercial No 100% Virgin Vinyl None		
Gloss Level			
Commercial Traffic			
Added Antimicrobial			
Recycled Contents			
Backstamp Info			
CE Certification	Yes		
Ceruncauon	DETAILS		
PACKING SPECIFICATIONS	Plank (7"x 48")	Tile (12" x 24")	ADDITIONAL INFORMATION
Pallet Dimensions (L x W x H)	1,260 x 1,010 x 757 (mm)	1,260 x 1,010 x 877 (mm)	
	+	+	
Square Feet per Plank/Tile	2.33	1.94	
Square Feet per Box	41.85	42.63	
Square Feet per Pallet	2,511.01	3,069.01	20 feet eesteinen
Square Feet per Container	40,176.08	42,966.08	20 foot container
Weight per sq ft (lbs.)	0.88	0.88	
Weight per Plank/Tile (lbs.)	2.04	1.70	
Weight per Box (lbs.)	36.74	37.42	
Weight per Pallet (lbs.)	2,204.50	2,694.38	
Weight per Container (lbs.)	35,271.94	37,721.38	
Pieces per Box	18	22	
Boxes per Pallet	60	72	
Box Type	Corrugated	Corrugated	
Pallet per Container	16	14	
Boxes per Container	960	1,008	
PRODUCT PERFORMANCE/TESTING	PERFORMANCE		ASTM REQUIREMENT
ASTM F2055 Size and Tolerance	Passes		As specified 0.016 in./lin.ft.
ASTM F386 Thickness	Passes		As specified 0.005 in./lin.ft.
ASTM F2055 Squareness	Passes Passes Passes 6 mm mandrel Passes		Max. 0.010 in.
ASTM F1914 Residual Indentation			Avg. < 8%
ASTM F137 Flexibility			1 in. (25.4 mm) mandrel/no crack or break
ASTM F2199 Dimension Stability			< 0.020 in./ft.
ASTM F925 Chemical Resistance	Passes		No change/slight change
ASTM F1514 Resistance to Heat	Passes Passes		< 8 (delta E) avg.
ASTM F1515 Resistance to Light			< 8 (delta E) avg.
ASTM E648 Critical Radiant Flux	Class 1		Class 1 (< 0.45 W/cm²)
ASTM E662 Optical Smoke Density	Passes		< 450
ASTM C1028 Slip Resistance	Passes		ADA Compliant (> 0.50)
•	1,000 psi		250 psi (< 0.005 in.)
ASTM F970 Static Load	DETAILS		ADDITIONAL INFORMATION
	DETAILS		
TECHNICAL INFORMATION/DOCUMENTS		/25 Years Residential	
TECHNICAL INFORMATION/DOCUMENTS Product Warranty	DETAILS 10 Years Heavy Commercial Full spread	/25 Years Residential	
TECHNICAL INFORMATION/DOCUMENTS Product Warranty Installation Method	10 Years Heavy Commercial Full spread		
TECHNICAL INFORMATION/DOCUMENTS Product Warranty	10 Years Heavy Commercial	e	







1364 Ash Grey Oak



1365 Golden Brown Oak



1372 Coastal Oak





1362 Feathered Oak



1373 Natural Wenge



1363 Grey Hickory





















Featured Color: 1369 Blue Grey Oak





















6371 Sirius 6372 Betelgeuse 6370 Arcturus











LX Hausys America, Inc. 900 Circle 75 Parkway, Suite 1500 Atlanta, GA 30339 Toll Free 866-544-4622 Email flooring@lxhausys.com www.lxhausys.com