



www.lxhausys.com

H·FLOR

Savana

SPC Plank And Luxury Vinyl Plank

Click 5 mm/12 mil

Gluedown 2 mm/12 mil



Resilient Flooring




Savana




 Plank 6 Colors



■ Product Configuration (SPC Click)



■ Product Configuration (LVP Gluedown)



■ Features

- EASY INSTALLATION WITH 5Gi LOCKING SYSTEM**
 - Shortens installation time and ensures flush joints
- HIGH-RESOLUTION REALITY IMAGE**
 - High-resolution photo quality printing is applied to elaborately express the reality of the material
- TRANSFERGUARD (PREVENTS FLOOR TRANSFER)**
 - Reduces prep time and ensures smooth installation (no “telegraphing”)

■ Features

- HIGH-RESOLUTION REALITY IMAGE**
 - High-resolution photo quality printing is applied to elaborately show the reality of the material
- ECO- & HUMAN-FRIENDLY**
 - FloorScore® and DIBt certified for low VOCs
 - Phthalate-Free (DEHP·DBP·BBP·DIDP·DINP·DNOP) & Heavy Metal-Free (Cd·Pb·Hg·Cr6+)
 - Made from 100% virgin vinyl
- EXCELLENT RESISTANCE TO WATER**
 - No swelling, no distortion



All specifications are subject to change without notice.
Application images are CGI renderings that are shown for illustration purpose only.
Printed representation of colors may vary from actual product. Please view the actual product prior to purchase.

Specifications

| | |
|------------------------|--------------------|
| COLLECTION NAME | Savana (SPC Click) |
| TOTAL # SKU'S (COLORS) | 6 |

| PRODUCT SPECIFICATIONS/CONTENT/CERTIFICATIONS | DETAILS | ADDITIONAL INFORMATION |
|---|---|------------------------------------|
| Thickness | 5.0 mm (0.197") | 1 mm IXPE Foam |
| Wear Layer | 12 mil (0.3 mm) | |
| Glass Fiber | N/A | |
| Finishing/Coating | Enhanced UV Urethane Coating | |
| Nominal Dimensions (inches) | 6" x 48" | |
| Actual Dimensions (mm) | 150 mm x 1,220 mm | |
| Micro-Beveled | Yes | |
| Class/ASTM F1700 | Class III Printed Film Vinyl Tile - Type B (embossed) | |
| Backing Class | IXPE Foam | |
| Gloss Level | 4 - 8 | |
| Commercial Traffic | Light Commercial | |
| Added Antimicrobial | No | |
| Recycled Contents | 100% Virgin Vinyl | |
| Backstamp Info | None | |
| CE Certification | Yes | |
| PACKING SPECIFICATIONS | DETAILS | ADDITIONAL INFORMATION |
| Pallet Dimensions (L x W x H) | 1,050 x 1,300 x 981 (mm) | |
| Square Feet per Plank/Tile | 1.97 | |
| Square Feet per Box | 23.64 | |
| Square Feet per Pallet | 1,701.92 | |
| Square Feet per Container | 27,230.68 | 20 foot container |
| Weight per sq. ft. (lbs.) | 1.54 | |
| Weight per Plank/Tile (lbs.) | 3.03 | |
| Weight per Box (lbs.) | 36.36 | |
| Weight per Pallet (lbs.) | 2,617.81 | |
| Weight per Container (lbs.) | 41,885.00 | |
| Pieces per Box | 12 | |
| Boxes per Pallet | 72 | |
| Box Type | Corrugated | |
| Pallets per Container | 16 | |
| Boxes per Container | 1,152 | |
| PRODUCT PERFORMANCE/TESTING | PERFORMANCE | ASTM REQUIREMENT |
| ASTM F2421 Size and Tolerance | Exceeds with 0.006 in. avg. | As specified 0.016 in./lin.ft. |
| ASTM F387 Thickness | Passes | As specified +/- 0.005 in./lin.ft. |
| ASTM F2421 Squareness | Exceeds with 0.003 in. avg. | Max. 0.010 in. |
| ASTM F1914 Residual Indentation | Exceeds with 0.001 in. | Avg.≤0.007 in. |
| ASTM F2199 Dimension Stability | 0 in. of change at 158°F | < 0.020 in./ft. |
| ASTM F2199 Dimension Stability | 0 in. of change at 158°F | Max. 0.080 in. |
| ASTM F925 Chemical Resistance | No Change | No change/slight change |
| ASTM F1514 Resistance to Heat | Exceeds with 0.36 (Delta E) | < 8 (delta E) avg. |
| ASTM F1515 Resistance to Light | Exceeds with 0.37 (Delta E) | < 8 (delta E) avg. |
| ASTM E648 Critical Radiant Flux | Exceeds NFPA 101 Class 1 Rating at 1.04 W/cm² | Class 1 (> 0.45 W/cm²) |
| ASTM E662 Optical Smoke Density Flaming | Passes with 342 Average Manixum Density | < 450 Average Manixum Density |
| ASTM E662 Optical Smoke Density Non-Flaming | Passes with 434 Average Manixum Density | < 450 Average Manixum Density |
| ASTM C1028 Slip Resistance | Exceeds Wet and Dry Conditions | ADA Compliant (> 0.50) |
| ASTM F970 Static Load | Exceeds at 0.002 in. | 250 psi (< 0.005 in.) |
| ASTM E490/E90 Sound Rating | 62/53 | As tested |
| ASTM F3261 Surface Integrity of Wear Layer | No puncture through wear layer | No puncture through wear layer |
| TECHNICAL INFORMATION/DOCUMENTS | DETAILS | ADDITIONAL INFORMATION |
| Product Warranty | 10 Years for Light Commercial/25 Years Residential | |
| Installation Method | Click | |
| Approved Installation Locations | Above, Below, and On-Grade | |
| Recommended Adhesive | No adhesive | |
| Polish Required (Yes/No) | No | |

| | |
|------------------------|-----------------------|
| COLLECTION NAME | Savana (LVP Gluedown) |
| TOTAL # SKU'S (COLORS) | 6 |

| PRODUCT SPECIFICATIONS/CONTENT/CERTIFICATIONS | DETAILS | ADDITIONAL INFORMATION |
|---|---|---|
| Thickness | 2.0 mm (0.0787") | |
| Wear Layer | 12 mil (0.3 mm) | |
| Glass Fiber | N/A | |
| Finishing/Coating | Enhanced UV Urethane Coating | |
| Nominal Dimensions (inches) | 6" x 48" | |
| Actual Dimensions (mm) | 150 mm x 1,200 mm | |
| Micro-Beveled | No | |
| Class/ASTM F1700 | Class III Printed Film Vinyl Tile - Type B (embossed) | |
| Backing Class | Commercial Grade | |
| Gloss Level | 4 - 8 | |
| Commercial Traffic | Light Commercial | |
| Added Antimicrobial | No | |
| Recycled Contents | 100% Virgin Vinyl | |
| Backstamp Info | None | |
| CE Certification | Yes | |
| PACKING SPECIFICATIONS | DETAILS | ADDITIONAL INFORMATION |
| Pallet Dimensions (L x W x H) | 1,260 x 1,010 x 770 (mm) | |
| Square Feet per Plank/Tile | 1.94 | |
| Square Feet per Box | 52.31 | |
| Square Feet per Pallet | 3,138.78 | |
| Square Feet per Container | 50,220.52 | 20 foot container |
| Weight per sq. ft. (lbs.) | 0.77 | |
| Weight per Plank/Tile (lbs.) | 1.49 | |
| Weight per Box (lbs.) | 40.17 | |
| Weight per Pallet (lbs.) | 2,410.09 | |
| Weight per Container (lbs.) | 38,561.50 | |
| Pieces per Box | 27 | |
| Boxes per Pallet | 60 | |
| Box Type | Corrugated | |
| Pallets per Container | 16 | |
| Boxes per Container | 960 | |
| PRODUCT PERFORMANCE/TESTING | PERFORMANCE | ASTM REQUIREMENT |
| ASTM F2055 Size and Tolerance | Passes | As specified 0.016 in./lin.ft. |
| ASTM F386 Thickness | Passes | As specified 0.005 in./lin.ft. |
| ASTM F2055 Squareness | Passes | Max. 0.010 in. |
| ASTM F1914 Residual Indentation | Passes | Avg. < 8% |
| ASTM F137 Flexibility | Passes 6 mm mandrel | 1 in. (25.4 mm) mandrel/no crack or break |
| ASTM F2199 Dimension Stability | Passes | < 0.020 in./ft. |
| ASTM F925 Chemical Resistance | Passes | No change/slight change |
| ASTM F1514 Resistance to Heat | Passes | < 8 (delta E) avg. |
| ASTM F1515 Resistance to Light | Passes | < 8 (delta E) avg. |
| ASTM E648 Critical Radiant Flux | Class 1 | Class 1 (< 0.45 W/cm²) |
| ASTM E662 Optical Smoke Density | Passes | < 450 |
| ASTM C1028 Slip Resistance | Passes | ADA Compliant (> 0.50) |
| ASTM F970 Static Load | 2,000 psi | 250 psi (< 0.005 in.) |
| TECHNICAL INFORMATION/DOCUMENTS | DETAILS | ADDITIONAL INFORMATION |
| Product Warranty | 10 Years Light Commercial/ 25 Years Residential | |
| Installation Method | Full spread | |
| Approved Installation Locations | Above, Below, and On-Grade | |
| Recommended Adhesive | Any approved LVT adhesive | |
| Polish Required (Yes/No) | No | |



Featured Color: 9125 Ambience



9131 Relax



9133 Sunshine



9135 Vintage



9121 Sunset



9123 Calm



9125 Ambience



Featured Color: 9135 Vintage

H·FLOR

by LX Hausys



LX Hausys America, Inc.
900 Circle 75 Parkway, Suite 1500
Atlanta, GA 30339
Toll Free 866-544-4622
Email flooring@lxhausys.com
www.lxhausys.com