

**LX Hausys America, Inc.**

900 Circle 75 Parkway, Suite 1500

Atlanta, GA 30339

866-544-4622

www.lxhausysusa.com

LX HAUSYS FLOORS ARTISTRY CLICK SPECIFICATION

COLLECTION NAME	Artistry Click
INVENTORY STYLE #	
STYLE NAME(s)	
SELLING STYLE #(s)	Artistry Click
TOTAL # SKU'S(COLORS)	12

PRODUCT SPECIFICATIONS / CONTENT / CERTIFICATIONS	DETAILS		ADDITIONAL INFORMATION
Thickness	6.0mm (0.236 in)		with 1.5mm IXPE Foam
Wear Layer	20mil (0.5mm)		
Glass Fiber			
Finishing / Coating	Stoneshield		
Nominal Dimensions (inches)	Plank(9" x 60"), Tile(12" x 24")		
Actual Dimensions (inches & mm)	Plank(228.6mm x 1,523mm), Tile(310mm x 605mm)		
Micro-Beveled	No		
Class / ASTM F3261	Class I - Type B(embossed), Grade 1, Backing Class B		
Backing Class	IXPE Foam		
Gloss Level	5~12		
Commercial Traffic	Residential / Commercial		
Added Antimicrobial	No		
Recycled Contents	100% Virgin Vinyl		
Backstamp info	None		
CE Certification	Yes		
PACKING SPEC'S	DETAILS		ADDITIONAL INFORMATION
	Plank(9"x 60")	Tile(12" x 24")	
Product dimension (Width, mm)	228.6	310.0	
Product dimension (Length, mm)	1,523.0	605.0	
Pallet Dimensions (L x W x H)	1,600 X 1,000 x 148 (mm)	1,300 X 1,050 x 148 (mm)	
Square feet per plank/tile [formula field]	3.748	2.019	
Square feet per carton	29.983	20.190	
Square feet per pallet	1,679.062	1,453.657	
Square feet per container [formula field]	23,506.861	23,258.516	20 foot container
Weight per sq ft(lbs) [formula field]	1.110	1.638	
Weight per plank/tile (lbs/plank)	4.161	3.307	
Weight per carton (lbs)	33.290	33.069	
Weight per pallet (lbs)	1,864.229	2,380.993	
Weight per container (lbs)	26,099.209	38,095.885	
Pieces per box	8	10	
Boxes per pallet	56	72	
Box Type			
Pallet per container	14	16	
Boxes per container [formual field]	784	1152	
PRODUCT PERFORMANCE / TESTING	PERFORMANCE		ASTM REQUIREMENT
ASTM F2055 Size and Tolerance	Passes		As speicfied 0.016 in.
ASTM F387 Thickness	Passes		As speicfied 0.008 in. (with foam)
ASTM F2055 Squareness	Passes		Max. 0.010 in.
ASTM F1914 Residual Indentation	Passes		Avg.≤0.007 in. (0.18mm)
ASTM F2199 Dimension Stability	Passes		<0.2%/ lineal ft(305mm)
ASTM F2199 Dimension Stability	Passes		Max. 0.080 in. (2mm)
ASTM F1914 Surface integrity	Passes		No puncture through wear layer / deco into rigid core
ASTM F925 Chemical Resistance	Passes		No change/Slight change
ASTM F1514 Resistance to Heat	Passes		<8 (delta E) avg.
ASTM F1515 Resistance to Light	Passes		<8 (delta E) avg.
ASTM E648 Critical Radiant Flux	Class 1		Class 1 (>0.45 W/cm ²)
ASTM E662 Optical Smoke Density	Passes		<450
ASTM C1028 Slip Resistance	Passes		ADA Compliant(>0.50)
ASTM F970 Static Load	Passes (500 psi with Foam)		250 psi(<0.005")
TECHNICAL INFORMATION / DOCUMENTS	DETAILS		ADDITIONAL INFORMATION
Product Warranty	10 years for Commercial		
Installation Method	Click		
Recommended Adhesive(s)	No Adhesives		
Polished Required (Y/N)	None		